



Briggs & Stratton Animal

Camshaft Profile Sheet

Name Driver/Handler: _____ Date: _____

Serial Number: _____

<u>INTAKE DEGREES</u>	<u>EXHAUST DEGREES</u>
0.005 54 TO 65 BTDC _____	0.005 277 TO 284.5 BTDC _____
0.020 12 TO 19 BTDC _____	0.020 235 TO 241 BTDC _____
0.050 1 TO 5 ATDC _____	0.050 219 TO 224 BTDC _____
0.100 17 TO 21 ATDC _____	0.100 202 TO 206 BTDC _____
0.150 32 TO 37 ATDC _____	0.150 186 TO 190 BTDC _____
0.200 53 TO 57 ATDC _____	0.200 166 TO 171 BTDC _____
0.225 _____ Split ATDC _____	0.225 _____ Split BTDC _____
0.258 MAX (104 TO 107 CL)	0.259 MAX (113 TO 116 CL)
0.225 _____ Split ATDC _____	0.225 _____ Split BTDC _____
0.200 154 TO 159 ATDC _____	0.200 58 TO 62 BTDC _____
0.150 174 TO 179 ATDC _____	0.150 38 TO 42 BTDC _____
0.100 191 TO 195 ATDC _____	0.100 22 TO 26 BTDC _____
0.050 208 TO 212 ATDC _____	0.050 5 TO 9 ATDC _____
0.020 225 TO 232 BTDC _____	0.020 7.5 TO 13 ATDC _____
0.005 269 TO 276.5 BTDC _____	0.005 47.5 TO 58 ATDC _____